



The Chemical Company

# MATERIAL SAFETY DATA SHEET

According to NOHSC: 2011 (2003) and HSNO CoP 8-1 (September 2006)

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: **CONIPUR TC 481 COMP B**

Other name: None allocated

Recommended use: Part B of a two-component, solvent containing polyurethane sealer.

Supplier: BASF Construction Chemicals Australia Pty Ltd. BASF New Zealand Ltd.  
ABN 46 000 450 288

Address: 11 Stanton Road, Seven Hills, NSW, 2147 Australia 45 William Pickering Drive, Albany, Auckland, New Zealand

Telephone number: +61 2 8811 4200 +64 9 414 7233

Facsimile: +61 2 8811 3299 +64 9 414 7244

Emergency telephone number: +61 417 658 263

## 2. HAZARDS IDENTIFICATION

Hazard classification: HAZARDOUS SUBSTANCE. DANGEROUS GOODS.  
Dangerous goods for transport according to the ADG code.  
Hazardous according to the criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001

Hazard Designation: Xn Harmful  
Flammable.  
May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment. Harmful by inhalation and in contact with the skin.

HSNO Classification

3.1C	Flammable liquid and vapour
6.1D	Acutely toxic (inhalation)
6.3A	Irritating to the skin
6.4A	Irritating to the eyes
6.5A	Respiratory sensitiser
6.5B	Contact sensitiser (dermal)
6.9	Irritating to the respiratory system

Risk phrase(s):

R10	Flammable
R20	Harmful by inhalation.
R22	Harmful by inhalation
R36/37/38	Irritating to eyes, respiratory system and skin.
R42/43	May cause sensitisation by inhalation and skin contact.

Safety phrase(s):

S2	Keep out of reach of children.
S3/7/9	Keep container tightly closed in a cool, well-ventilated place.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S35	This material and its container must be disposed of in a safe way.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

# MATERIAL SAFETY DATA SHEET

According to NOHSC: 2011 (2003) and HSNO CoP 8-1 (September 2006)

S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well ventilated areas.
S63	In case of accident by inhalation, remove casualty to fresh air and keep at rest.
S64	If swallowed, rinse mouth with plenty of water (only if the person is conscious)

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

**Chemical Characterisation:** Aliphatic isocyanate prepolymer with slight monomeric parts. Contains solvent

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Proportion</u>
Aliphatic Polyisocyanate	28128-81-2	25 – 50%
Xylene	1330-20-7	10 – 25%
Hexamethylene Di-Isocyanate	822-06-0	0.1 – 0.5%
Non hazardous ingredients		To 100%

### 4. FIRST AID MEASURES

<u>Inhalation:</u>	Take the casualty into the fresh air and keep warm. Keep at rest. If breathing is difficult, give oxygen. Seek medical attention immediately.
<u>Eyes:</u>	While holding eyes open, gently flood with plenty of fresh water for 15 minutes. Seek medical attention. Skilled personnel should only undertake removal of contact lenses after an eye injury.
<u>Skin:</u>	Immediately remove all contaminated clothing. Wash contacted area thoroughly with soap and plenty of water and rinse. Do NOT use solvents or thinners. Seek medical attention in the event of irritation.
<u>Ingestion:</u>	Not a normal route of injury. Contact a doctor immediately. Do NOT induce vomiting. Wash mouth with water and seek medical attention immediately.

### 5. FIRE FIGHTING MEASURES

<u>Suitable extinguishing media:</u>	Alcohol resistant foam, CO <sub>2</sub> , Dry Chemical and Water Spray. Do not use Water Jet.
<u>Hazards from combustion products:</u>	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. During a fire, carbon monoxide, nitrogen oxide, isocyanate vapours and traces of hydrogen cyanide may be given off.
<u>Precautions and equipment for fire fighters:</u>	Appropriate breathing apparatus may be required. Cool endangered containers with water in case of fire. Do not allow the extinguishing water into the sewage system.
<u>Hazchem code:</u>	3Y

### 6. ACCIDENTAL RELEASE MEASURES

<u>Methods and materials for containment and clean up:</u>	Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Small or major spills should be adsorbed with dry, inert filler (e. vermiculite, soil or sand), which can then be shovelled into appropriately labelled drums for disposal according to local regulations (see Section 13). Do not seal drums as carbon dioxide may be given off.
<u>Environmental precautions:</u>	Do not allow to enter into drains, sewers or waterways. If the product contaminates lakes, rivers or sewage system, inform appropriate authorities in accordance with local regulations.

# MATERIAL SAFETY DATA SHEET

According to NOHSC: 2011 (2003) and HSNO CoP 8-1 (September 2006)

## 7. HANDLING AND STORAGE

Precautions for safe handling: Provide for fresh air ventilation. Do not inhale the vapour. Avoid contact with skin and eyes. Do not eat, drink or smoke while working with this material or while working in the general area during application. Wash hands thoroughly before eating, drinking or smoking. Use a barrier cream before and after working with this product. Comply with all health and safety at work laws.

Conditions for safe storage: Store in a cool, dry and well ventilated area. Containers should be kept dry and sealed. Store under cover and away from direct sunlight, heat and moisture. Containers that are opened must be carefully resealed and kept upright to prevent leakage. Store away from strong oxidising agents, alcohols, strongly alkaline and strongly acidic materials. Store at 5 - 35°C. Avoid long-term exposure to elevated temperature (> 50°C). Avoid cooling to under 0°C. Keep out of reach of children.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particles below the OEL (Occupational Exposure Limit), suitable respiratory protection must be worn. Sensitised persons are not recommended to work with this product.

Exposure Standards Isocyanates, all (Sensitiser)

ES-TWA: 0.2 mg/m<sup>3</sup>ES STEL: 0.7 mg/m<sup>3</sup>NZ WES TWA: 0.2 mg/m<sup>3</sup>NZ WES STEL: 0.7 mg/m<sup>3</sup>

Personal Protective Equipment (PPE):

Respiratory protection: If spraying: air supplied respirator. Other operations than spraying: If workplace is well ventilated, air supplied respirators could be replaced by a combination of charcoal filter and particulate filter mask. Refer to specialist mask supplier.

Glove type (AS2161): Butyl rubber gauntlets (>= 0.5 mm for >= 480 min). When using other gloves with a lower endurance, change them more often.

Eye protection: Safety goggles, safety glasses with side-shields, face shield.

Clothing: Overalls or similar light protective clothing.

Other: Use barrier creams to protect skin from contact with the material. Always wash hands before smoking, eating, drinking or using the toilet and after finishing work. Observe the usual precautions when handling chemicals.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear to light yellow liquid.

Odour: Like solvent.

pH: Not applicable

Boiling point: Not available.

Viscosity: ca. 200 mPa.s. (20°C)

Solubility in water: Insoluble.

Specific gravity: ca 1.07 (20°C)

Flash point: ca. 43°C DIN 53213

# MATERIAL SAFETY DATA SHEET

According to NOHSC: 2011 (2003) and HSNO CoP 8-1 (September 2006)

Flammability limits: UEL – not available  
LEL – not available.

## 10. STABILITY AND REACTIVITY

Chemical stability: Stable under recommended storage and handling conditions (see Section 7).  
Incompatible materials: Keep away from oxidising agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions.  
Hazardous decomposition products: Carbon monoxide, carbon dioxide, smoke and oxides of nitrogen.  
Hazardous reactions: Exothermic reaction with incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

Health Hazard Summary: Not available  
Inhalation: The vapour is likely to be irritating to the respiratory system.  
Eyes: Eye contact may cause irritation.  
Skin contact: Mild skin irritation and redness from prolonged contact.  
Ingestion: The product is harmful by ingestion.  
Toxicity Data: Not available

## 12. ECOLOGICAL INFORMATION

Ecotoxicity: Do not discharge in to sewers or drains.

## 13. DISPOSAL CONSIDERATIONS

Disposal method and containers: Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.  
Special precautions (landfill/incineration): None known

## 14. TRANSPORT INFORMATION

UN number: 1993.  
UN proper shipping name: FLAMMABLE LIQUID N.O.S (CONTAINS XYLENE).  
Dangerous goods class: 3  
Subsidiary risk: III  
Packing group: None allocated.  
Hazchem code: 3Y

## 15. REGULATORY INFORMATION

NICNAS / AICS: All components are listed  
Poisons Schedule: Not Scheduled  
HSNO Classifications: 3.1C, 6.1D, 6.3A, 6.4A, 6.5A, 6.5B, 6.9  
ERMA Group Standard: HSR002544



The Chemical Company

# MATERIAL SAFETY DATA SHEET

According to NOHSC: 2011 (2003) and HSNO CoP 8-1 (September 2006)

ERMA / NZIoC: All components are listed  
Tracking: Not required  
Approved Handler: Not required

## 16. OTHER INFORMATION

Reason for issue: Update to combined Australia and New Zealand MSDS.

This MSDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request. All information contained in this MSDS is as accurate and up-to-date as possible. No warranty expressed or implied is made as to its accuracy, reliability or completeness.