



The Chemical Company

MASTERPREN[®] 2000 PRIMER

High quality solvent based bituminous primer

DESCRIPTION

MASTERPREN 2000 Primer is a low viscosity, black priming solution designed to deeply penetrate and seal porous surfaces to provide a base for bituminous waterproofing and protection systems.

MASTERPREN 2000 Primer is a blend of high quality bitumen and hydrocarbon solvents.

RECOMMENDED FOR

MASTERPREN 2000 Primer is used prior to the application of a wide range of BASF bituminous products. **MASTERPREN 2000 Primer** when applied to porous substrates, seals and improves the adhesion of waterproofing and protection systems, which include:

- **MASTERPREN** torch-on and traditional build-up roofing felts
- **MASTERPREN** self-adhesive damp-proof membranes and flashings

APPLICATION

Surface Preparation

Surfaces, onto which **MASTERPREN 2000 Primer** is applied must be clean and free from dirt, dust, grease or other material, which may impair adhesion. If moss or fungus is present, this should be removed and the substrate treated with fungicide applied in accordance with its application instructions.

Placing

MASTERPREN 2000 Primer can be applied by roller, squeegee or spray, to damp (not wet) or dry surfaces. **MASTERPREN 2000 Primer** dries quickly and is resistant to rainfall 20-30 minutes after application.

CLEANING

Tools and equipment may be cleaned using white spirit or paraffin.

ESTIMATING DATA

Metal Surfaces: 12-16m²/L

Porous Surfaces 6-8m²/L

PACKAGING

MASTERPREN 2000 Primer is available in 20 litre cans.

SHELF LIFE

MASTERPREN 2000 can be stored for 12 months if stored in original unopened packaging in cool conditions.

PRECAUTIONS

For the full health and safety hazard information and how to safely handle and use this product, please make sure that you obtain a copy of the BASF Construction Chemicals **Material Safety Data Sheet (MSDS)** from our office or our website.



The Chemical Company

MASTERPREN[®] 2000 PRIMER

AMpren2000Primer/3/1111

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this **BASF** publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by **BASF** either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not **BASF**, are responsible for carrying out procedures appropriate to a specific application.

BASF Australia Ltd

A.B.N. 62008437867

Head Office: 11 Stanton Road Seven Hills, NSW 2147

Ph. (02) 8811 4200

Newcastle (02) 4961 3819

Canberra (02) 6280 6010

Brisbane (07) 3633 9900

Townsville (07) 4774 7344

Melbourne (03) 9549 0300

Adelaide (08) 8139 7500

Perth (08) 9366 2600

Darwin (08) 8984 3269

Kalgoorlie 0417 772 355

BASF New Zealand Ltd

BASF WEB SITES

Head Office: 45 William Pickering Drive, Albany, Auckland Ph: (09) 414 7233

www.basf-cc.com.au

www.basf-cc.co.nz

www.meyco.basf.com
